



IDE FLOORING ADHESIVE RECOMMENDATION

Stand 15.01.2024

LIZIN UTZ®
YOUR FLOOR. OUR PASSION.

UZIN ADHESIVE RECOMMENDATION IDE FLOORING



Product	Adhesive recommendation	Toothting
Futura PPublic	UZIN KE 68 UZIN KE 2000 S	A2 / A5

Preparation of the substrate

The substrate must comply with and be prepared in accordance with the generally accepted rules of the trade and technology for laying parquet and floor coverings in accordance with the applicable national standards (e.g. EN, DIN, Ö-Norm, SIA, etc.). In particular, the substrate must be level, permanently dry, solid, load-bearing, free of release agents and cracks, and resistant to tension and compression, or must be prepared accordingly. In order to be able to offer a guarantee in the system, the filling work should be carried out with the suitable UZIN filling compounds in conjunction with UZIN primers.

The UZIN System

Floor covering work is carried out with suitable UZIN adhesives. The technical UZIN data sheets of the products must be observed. The processing recommendations are based on tests and practical experience. They represent general information without guarantee of properties, since UZIN has no influence on the site conditions and the execution of the work. Country-specific regulations based on regional standards, building regulations, processing or industry guidelines may lead to specific processing recommendations.

UZIN offers relevant system solutions of the highest quality for bonding and adhesion of floors and parquet.
For further information on our products, including emission behavior, test seals and certifications, product properties, processing instructions, as well as application examples and details on occupational safety and environmental protection and disposal on occupational health and safety, environmental protection and disposal can be found in the respective product data sheet or the safety data sheet and test certificates at www.uzin.de/produkte.
UZIN is a brand of the Uzin Utz Group. Uzin Utz Aktiengesellschaft | Dieselstraße 3 | D-89079 Ulm | Postfach 40 80 | D-89030 Ulm | Phone +49 (0)731 4097-0 | Fax +49 (0)731 4097-410 | E-mail info@uzin-utz.com

CONTACT PERSONS



THOMAS SCHNEIDER

Head of UZIN Application Technology

T +49 731 4097-223

thomas.schneider@uzin-utz.com

ROBIN GABEL

UZIN Technical Customer Service

T +49 731 4097-260

robin.gabel@uzin-utz.com

LIZINTZ®

YOUR FLOOR. OUR PASSION.



WOLFF®



PALLMANN®



codex®



Pajarito®